

NEREZOVÉ PŘÍSTROJOVÉ KLDKY

- nerezové pouzdro AISI 304
- otočné ložisko tvořeno dvěma kuličkovými dráhami
- polyamidové kolo s nerezovým kluzným ložiskem



otočná kladka

392a00I060pEPC	60	22	89	26		60x60	45x45	6,5	40
392a00I080pEPC	80	22	109	27		60x60	45x45	6,5	50
392a00I100pEPD	100	27	134	36		76x70	60x50	8,3	55
392a00I125pEPD	125	27	158	34		76x70	60x50	8,3	65



otočná kladka s úplnou blokací

392h00I060pEPC	60	22	89	26		60x60	45x45	6,5	40
392h00I080pEPC	80	22	109	27		60x60	45x45	6,5	50
392h00I100pEPD	100	27	134	36		76x70	60x50	8,3	55
392h00I125pEPD	125	27	158	34		76x70	60x50	8,3	65



pevná kladka

391a00I060pEPC	60	22	89			60x60	45x45	6,5	40
391a00I080pEPC	80	22	109			60x60	45x45	6,5	50
391a00I100pEPD	100	27	134			76x70	60x50	8,3	55
391a00I125pEPD	125	27	158			76x70	60x50	8,3	65



otočná kladka

392a00I060pELD	60	22	88	26	12				40
392a00I080pELD	80	22	108	27	12				50
392a00I100pELD	100	27	132	36	12				55
392a00I125pELD	125	27	156	34	12				65



otočná kladka s úplnou blokací

392h00I060pELD	60	22	88	26	12				40
392h00I080pELD	80	22	108	27	12				50
392h00I100pELD	100	27	132	36	12				55
392h00I125pELD	125	27	156	34	12				65