



mm



mm



mm



mm



kg



• polyamidové kolo s válečkovým ložiskem

00R080p-44-12	80	32	44	12	180
00R100p-44-12	100	32	44	12	190
00R125p-44-12	125	32	44	12	270
00R125p-58-20	125	45	58	20	270
00R160p-58-20	160	45	58	20	350
00R200p-58-20	200	50	58	20	500



• polyamidový disk s válečkovým ložiskem a polyuretanovým běhounem, Shore A96

04R080v-44-12	80	32	44	12	140
04R100v-44-12	100	32	44	12	150
04R125v-44-12	125	32	44	12	190
04R125v-58-20	125	45	58	20	300
04R160v-58-20	160	38	58	20	300
04R200v-58-20	200	50	58	20	450



• "sandwichové" polyamidové kolo s válečkovým ložiskem a středovou výztuží z elastické pryže

0RR100p-45-12	100	36	45	12	160
0RR125p-45-12	125	36	45	12	200



• polyamidový disk s válečkovým ložiskem a pneumatikou

27R200I-60-20	200	50	60	20	75
27R260I-75-20	260	85	75	20	150
27R400I-75-20	400	100	75	20	200



• ocelový lakovaný disk s válečkovým ložiskem a pneumatikou

28R200I-60-20	200	50	60	20	75
28R260I-75-20	260	85	75	20	150
28R400I-75-20	400	100	75	20	200