

TRANSPORTNÍ KOLA



mm



mm



mm



mm



kg



• polypropylenový disk s válečkovým ložiskem a pryžovou obručí, Shore A80

07R080c-44-12	80	30	44	12	60
07R100c-44-12	100	30	44	12	70
07R125c-44-12	125	37	44	12	100
07R160c-58-20	160	38	58	20	135
07R200c-58-20	200	46	58	20	205



polypropylenový disk s válečkovým ložiskem a bezstopou pryžovou obručí, Shore A80

07R080b-44-12	80	30	44	12	60
07R100b-44-12	100	30	44	12	70
07R125b-44-12	125	37	44	12	100
07R160b-58-20	160	38	58	20	135
07R200b-58-20	200	46	58	20	205



• ocelový zinkovaný disk s válečkovým ložiskem a pryžovou obručí, Shore A80

08R080c-44-12	80	30	44	12	60
08R100c-44-12	100	30	44	12	70
08R125c-44-12	125	37	44	12	100
08R160c-58-20	160	38	58	20	135
08R200c-58-20	200	46	58	20	205



• ocelový zinkovaný disk s válečkovým ložiskem a bezstopou pryžovou obručí, Shore A80

08R080b-44-12	80	30	44	12	60
08R100b-44-12	100	30	44	12	70
08R125b-44-12	125	37	44	12	100
08R160b-58-20	160	38	58	20	135
08R200b-58-20	200	46	58	20	205



• polypropylenový disk s válečkovým ložiskem a bezstopým TPE běhounem, Shore A85

06R080r-44-12	80	32	44	12	70
06R100r-44-12	100	32	44	12	80
06R125r-44-12	125	32	44	12	100
06R125r-58-20	125	45	58	20	150
06R160r-58-20	160	45	58	20	200
06R200r-58-20	200	50	58	20	200



• polypropylenový disk s válečkovým ložiskem a bezstopou obručí z elastické pryže, Shore A75

14R080d-44-12	80	36	44	12	130
14R100d-44-12	100	36	44	12	140
14R125d-44-12	125	36	44	12	180
14R125d-58-20	125	50	58	20	250
14R160d-58-20	160	50	58	20	300
14R200d-58-20	200	50	58	20	400



• polypropylenové kolo s válečkovým ložiskem

00R080z-44-12	80	32	44	12	120
00R100z-44-12	100	32	44	12	150
00R125z-44-12	125	32	44	12	160
00R125z-58-20	125	45	58	20	170
00R160z-58-20	160	45	58	20	190
00R200z-58-20	200	50	58	20	200